


# **JUICE BOOSTER 3 air**

# The mobile wall box for all occasions



#### Wall box

The JUICE BOOSTER 3 air can be used as a wall charging station in conjunction with the specially developed holder.

#### **RFID** activation

RFID reader in the Type 2 connector. Two RFID cards are included free of charge.



# Type 2 cable

Just one cable needed: With the JUICE BOOSTER 3 air and the Type 2 adapter, you no longer require a separate Type 2 cable for public charging stations.

## Small and handy

Up to 10 times smaller than other mobile charging stations. Feather-light with a weight of less than 1 kg.



# Clean and tidy

Included free of charge: robust case with integrated Velcro strips for secure boot storage.

### **JUICE CELSIUS**

The JUICE CELSIUS temperature sensor integrated in domestic adapters detects overheating (e.g. in the case of poorly wired plug sockets) and thus protects against potential fires.

value.

costs of up to 1000 euros/francs.

The DC and AC fault detection trips effectively at the prescribed

The integrated safety function eliminates the need for an expensive Type B residual current device in your home. This saves you

#### Individuality

Compatible with all electric vehicles with a Type 2 connection. Single-phase to three-phase charging possible at up to 16 amps – with 3.7/7.4 or 11 kW. Under ideal conditions, your battery will be fully charged in just 1 to 4 hours (depending on size).

In short, the JUICE BOOSTER 3 air is the perfect charging station for all applications.

# 5-metre cable length

The length can even be increased to 25 m using an extension cable.

## Programmable button

On the Type 2 connector for setting the power level, stopping charging or releasing the connector.

### 100% compatible

with all electric vehicles fitted with a Type 2 connector.

#### Communication

Bluetooth and WiFi for simple load management and remote control.



Automatic adapter detection with fully automatic adjustment of charging capacity.



#### JUICE CONNECTOR



Download the app today and dive into the world of j+ pilot.

The j+ pilot app allows you to control all

the functions of your JUICE BOOSTER 3 air: activation, time-controlled charging, current control, charging progress, statis-

are being added on a continuous basis.




# Adapter lock

Theft protection at home and on the road.



# **Extremely robust**

Able to withstand wheel loads of up to 3 tonnes.



Comprehensive fault detection and protection against incorrectly connected



# Mobile charging station

A comprehensive choice of adapters for all conventional domestic and industrial sockets ensures carefree charging all across the globe.



## Technical **specifications**

Dimensions	Diameter: 53 mm, length: 213 mm, cable length: 5 m
Weight	approx. 700 g without cable, approx. 1.8 kg with cable
Rated current	6 A to 16 A (20 A as Mode 3 charging cable)
Mains voltage	230 V (1-phase) / 400 V (3-phase)
Communication	Bluetooth, WiFi
Fault identification	10 individual fault identifications, incl.
Interruption in the case	e of overheated domestic sockets
Safety cut-out for inco	rrectly wired sockets
Safety cut-out for excessive vehicle current draw	

Waterproof

Can be used in any weather.

CE conformity	IEC 62752, IEC 61851, EMV, RoHS
Protection rating - RCD	IP67 - RCD DC 6mA, RCD AC 30mA
Activation	RFID reader in Type 2 connector (ISO 14443 Type A)
Mains connectors	More than 30 self-detecting adapters available for domestic, industrial and EV sockets, approx. $30\mathrm{cm}$ adapter length
Vehicle-side con- nection	Type 2 (EN 62196)
Power levels	0A/6A/8A/10A/13A/16A
Material, colour	Anodised aluminium, anthracite

