


JUICE BOOSTER 2

The portable wallbox for anywhere and everywhere




Wallbox

The JUICE BOOSTER 2 can also be used as a wall-mounted charging station by fitting the specially designed holder bracket.


The adapter lock

The ultimate theft deterrent for private use or in public places.



JUICE CONNECTOR

Automatic adapter recognition with fully automatic charging power adjustment.



30+

others


Portable charging station

Charge your car worldwide worry-free thanks to the comprehensive assortment of adapters for all standard household and industrial socket outlets.



The cable length can even be extended to as much as 25 m by using an extension cable.

(Extension cable not provided for in the standard, so it carries no CE marking.)



100% compatible

with all electric vehicles fitted with a Type 2 connector. Also available with a Type 1 connector.

Individual design



kind of weather.

§ JUICE-CELSIUS

The JUICE CELSIUS temperature sensor integrated into household adapters detects any overheating (e.g. in poorly wired power sockets), thereby preventing potential fires.



Ultra-light

Weighs in at less than 1 kg.



carrier bag with integrated wheel loads Velcro strips for optimum Driveover-resistant even storage in the boot. to heavy wheel loads.



Type 2 cable

Only one cable required: With the JUICE BOOSTER 2 and Type 2 adapter, you no longer need any separate Type 2 cable, even for public charging stations.

Integral residual current detection

DC and AC fault detection trips effectively at the specified value.



Technical specifications

D: :	Di 1 70 1 11 005
Dimensions	Diameter: 70 mm, Length: 225 mm
Weight	1,0 kg excluding cables, 3,2 kg with cables and plugs
Power	1,4 kW-22 kW AC
Rated current	6 A to 32 A
Mains voltage	230 V (single-phase) / 400 V (3-phase)
Material - colour	Anodised aluminium, anthracite
Operating ambient	-30°C to +50°C
temperature	

CE conformity	IEC 62752, 62196, 61851-1, Mode 2/3, EMC, RoHS
Protection rating - RCD – safety	IP67 - RCD DC 6mA, AC 30mA - Earth conductor, temperature monitoring
Mains-end plug	Over 30 self-detecting adapters are available for domestic, industrial and EV sockets, 1,4 m power cable + approx. 30 cm adapter
Vehicle-end connector	Type 2 (EN 62196) / Type 1 (SAE J1772), cable length 3,1 m



JUICE BOOSTER 2

Travel without a care in the world

